

AMENDMENT TO CLAIMS

Please cancel claims 33 and 41-42 and add claims 43-45. All pending claims are reproduced below, including those that remain unchanged.

1. (Previously Presented) A system implemented using a computer to process XML document, comprising:

a streaming parser operable to parse an XML document to generate a stream of events, wherein each event in the stream represents a portion of the document;

a matching component to perform the steps of:

accepting an event from the stream of events from the streaming parser at one time;

keeping in memory only said event of the stream of events at any said time;

performing a match that is associated with an XQuery method on said event of the stream of events; and

notifying an observer when the event is a matched event, wherein when the event is not a matched event the observer is not notified;

said observer operable to listen for the matched event and passing it to a user object; and

said user object operable to handle the matched event.

2. (Previously Presented) The system according to claim 1, wherein:

the XML document is represented in a hierarchical structure.

3. (Previously Presented) The system according to claim 2, wherein:

the hierarchical structure is a tree with each node containing a portion of the document.

4. (Previously Presented) The system according to claim 3, wherein:

the streaming parser generates the stream of events by:

traversing the XML tree and adding visited nodes into a data structure;

processing the nodes in the data structure and generating an event for each node;

and

appending the event to the output stream.

5. (Previously Presented) The system according to claim 4, wherein:
the tree is traversed using a breath-first or depth-first search.
6. (Previously Presented) The system according to claim 4, wherein:
the data structure is a queue.
7. (Previously Presented) The system according to claim 4, wherein:
the data structure is processed using a first-in-first-out approach.
8. (Previously Presented) The system according to claim 1, wherein:
the matching component keeps only a portion of the XML document in memory at any given time.
9. (Previously Presented) The system according to claim 1, wherein:
the matching component knows the schema of the XML document and foreseeing the coming events.
10. (Previously Presented) The system according to claim 1, wherein:
the match is an expression-based match, which can be an XPath query.
11. (Previously Presented) The system according to claim 3, wherein:
the matching component keeps, clones and destroys the entirety or a portion of the subtree descending from a node in the tree.
12. (Previously Presented) The system according to claim 1, wherein:
the user object returns the matched event to an XML stream for use by any other component.

13. (Previously Presented) A method for processing XML document, comprising:
 - parsing an XML document to generate a stream of events, wherein each event in the stream represents a portion of the document;
 - accepting an event from the stream of events and keeping in memory only said event of the stream of events at one time;
 - performing a match that is associated with an XQuery method on said event of the stream of events;
 - notifying an observer when the event is a matched event, wherein when the event is not a matched event the observer is not notified;
 - listening for the matched event and passing it to a user object; and
 - handling the matched event.
14. (Previously presented) The method according to claim 13, further comprising:
 - representing the XML document in a hierarchical structure, which is a tree with each node containing a portion of the document.
15. (Original) The method according to claim 14, wherein:
 - the parsing of the XML document comprises the steps of:
 - traversing the XML tree and adding visited nodes into a data structure;
 - processing the nodes in the data structure and generating an event for each node;
 - and
 - appending the event to the output stream.
16. (Original) The method according to claim 15, wherein:
 - the XML tree is traversed using a breath-first or depth-first search.
17. (Original) The method according to claim 15, wherein:
 - the data structure is processed using a first-in-first-out approach.
18. (Original) The method according to claim 13, further comprising:

keeping only a portion of the XML document in memory at any given time.

19. (Original) The method according to claim 13, further comprising:

knowing the schema of the XML document and foreseeing the coming events.

20. (Previously presented) The method according to claim 13, further comprising:

performing an expression-based match, which is an XPath query.

21. (Original) The method according to claim 14, further comprising:

keeping, cloning and destroying the entirety or a portion of the sub-tree descending from a node in the tree.

22. (Previously presented) The method according to claim 13, further comprising:

returning the matched event to an XML stream for use by any other component.

23. (Previously Presented) A machine readable medium having instructions stored thereon that when executed by a processor to:

parse an XML document to generate a stream of events, wherein each event in the stream represents a portion of the document;

accept an event from the stream of events and keeping in memory only said event of the stream of events at one time;

perform a match that is associated with an XQuery method on said event of the stream of events;

notify an observer when the event is a matched event, wherein when the event is not a matched event the observer is not notified;

listen for the matched event and pass it to a user object; and

handle the matched event.

24. (Original) The machine readable medium of claim 23, further comprising instructions that when executed cause the system to:

represent the XML document in a hierarchical structure, which can be a tree with each node containing a portion of the document.

25. (Original) The machine readable medium of claim 24, further comprising instructions that when executed cause the system to:

parse the XML document, comprising the steps of:

traversing the XML tree and adding visited nodes into a data structure;

processing the nodes in the data structure and generating an event for each node;

and

appending the event to the output stream.

26. (Original) The machine readable medium of claim 25, further comprising instructions that when executed cause the system to:

traverse the tree using a breath-first or depth-first search.

27. (Original) The machine readable medium of claim 25, further comprising instructions that when executed cause the system to:

process the data structure using a first-in-first-out approach.

28. (Previously presented) The machine readable medium of claim 23, further comprising instructions that when executed cause the system to:

perform an expression-based match, which is an XPath query.

29. (Original) The machine readable medium of claim 23, further comprising instructions that when executed cause the system to:

keep only a portion of the XML document in memory at any given time.

30. (Original) The machine readable medium of claim 23, further comprising instructions that when executed cause the system to:

know the schema of the XML document and foresee the coming events.

31. (Original) The machine readable medium of claim 24, further comprising instructions that when executed cause the system to:
- keep, clone and destroy the entirety or a portion of the sub-tree descending from a node in the tree.
32. (Previously presented) The machine readable medium of claim 23, further comprising instructions that when executed cause the system to:
- return the matched event to an XML stream for use by any other component.
33. (Canceled).
34. (Canceled).
35. (Previously Presented) The system according to claim 1, wherein:
- said matching component can perform the step of accepting another event at said time.
36. (Previously Presented) The system according to claim 1, wherein:
- said matching component can perform the step of accepting another event at a different time.
37. (Previously presented) The method according to claim 13, further comprising:
- accepting another event at said time.
38. (Previously presented) The method according to claim 13, further comprising:
- accepting another event at a different time.
39. (Previously presented) The machine readable medium of claim 23, further comprising instructions that when executed cause the system to:
- accept another event at said time.

40. (Previously presented) The machine readable medium of claim 23, further comprising instructions that when executed cause the system to:
accept another event at a different time.

41. (Canceled).

42. (Canceled).

43. (New) A method for processing XML document, comprising:

parsing an XML document to generate a stream of events, wherein each event in the stream represents a portion of the document;

accepting an event from the stream of events and keeping in memory only said event of the stream of events at one time;

performing a match on said event of the stream of events and notifying an observer when the event is a matched event, wherein when the event is not a matched event the observer is not notified;

listening for the matched event and passing it to a user object that handles the matched event; and

returning said event to the stream of events; and

pulling said event from the stream of events for the use of a subsequent object.

44. (New) The method according to claim 43, wherein:

the subsequent object handles said event when there is another match.

45. (New) The method according to claim 43, further comprising:

keeping only a portion of the XML document in memory at any given time.